



# Desktop Manager

- Compact A4 multifunctionality.
- Fast and efficient output performance of up to 30 pages per minute.
- MFP with network capability as standard.
- Energy Save Mode for reduced power usage.

**e-STUDIO224cs**  
**e-STUDIO264cs**





**e-STUDIO224cs**  
**e-STUDIO264cs**



<p><b>General</b></p>	<p><b>Print Speed</b> Colour: 22/26 ppm B&amp;W: 24/30 ppm</p> <p><b>Copy Speed</b> Colour: 20/20 ppm B&amp;W: 24/30 ppm</p> <p><b>Warm-up Time</b> Approx. 32 seconds from power save mode</p> <p><b>Paper Size &amp; Weight</b> Cassettes: A6-A4, 64-176 g/m<sup>2</sup> Bypass: A6-A4, 64-220 g/m<sup>2</sup>, banner paper (up to 216 x 1,320 mm, 64-128 g/m<sup>2</sup>), labels, envelopes</p> <p><b>Paper Capacity</b> 1 x 250 sheets (cassette), 100 sheets (Bypass)</p> <p><b>Automatic Duplex</b> Maximum: 880 sheets</p> <p><b>Memory</b> A5-A4, 64-176 g/m<sup>2</sup> 256 MB, max. 768 MB 4 GB SD card memory<sup>2)</sup> max. 16 GB<sup>1)</sup></p> <p><b>Interface</b> USB 2.0 High Speed, 10/100BaseTX</p> <p><b>Dimensions &amp; Weight</b> 427 x 509 x 444 mm (W x D x H), ~ 29 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b> Max. 1,200 x 600 dpi</p> <p><b>First Print Output Time</b> Colour: Approx. 9/8 seconds B&amp;W: Approx. 8.5/7.5 seconds</p> <p><b>Page Description Languages</b> PCL6 (XL3.0 &amp; PCL5c) and PostScript 3 compatible</p> <p><b>Supported Systems</b> Windows 8/7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Server 2012/ Server 2008 R2 (64 bit), Mac OS 10.3.9 to 10.8, SAP, Unix/Linux</p> <p><b>Print Functions</b> Barcode Printing, Duplex Printing</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi</p> <p><b>Scan Speed</b> Colour: 3 sec/page (300 dpi) Grey: 2 sec/page (300 dpi)</p> <p><b>Document Feeder</b> Simplex: 50 sheets, A6-A4, 60-105 g/m<sup>2</sup> Duplex: 50 sheets, A5-A4, 60-90 g/m<sup>2</sup></p> <p><b>Scan Modes</b> Colour, Greyscale, B&amp;W</p> <p><b>File Formats</b> TIFF, PDF, Secure PDF, JPEG, XPS</p> <p><b>Scan Functions</b> Scan to E-Mail, Scan to File (CIFS, FTP), Scan to USB, Edge Erase, WIA, TWAIN</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Scan: max. 600 x 600 dpi Print: max. 1,200 x 600 dpi</p> <p><b>First Copy Output Time</b> Colour: Approx. 14 seconds B&amp;W: Approx. 12 seconds</p> <p><b>Zoom</b> 25-400%</p> <p><b>Copy Modes</b> Text, Text/Photo, Photo, Photo (Glossy)</p> <p><b>Colour Settings</b> Contrast, Hue, Saturation, RGB</p> <p><b>Copy Functions</b> Duplex Copy, ID Card Copy, Multiple Pages Per Sheet, Mixed Size Copy, Background Removal, Edge Erase, Continuous Scan, Repeat</p>
<p><b>Fax<sup>2)</sup></b></p>	<p><b>Communication</b> Super G3, G3, Internet Fax T.37</p> <p><b>Transmission Speed</b> Approx. 2 seconds per page (JBIG)</p> <p><b>Compression</b> JBIG, MMR, MR, MH</p> <p><b>Network-Fax</b> Windows 8/7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Server 2012/Server 2008 R2 (64 bit)</p> <p><b>Fax Functions</b> One Touch Dialing, Speed Dial (100 destinations), ECM, Polling, Group Dialing, Duplex In and Out</p>
<p><b>System</b></p>	<p><b>Device Management</b> e-BRIDGE Fleet Management System<sup>1)</sup></p> <p><b>System Features</b> LDAP support, local E-mail address book (max. 100 entries), user authentication, SNMP support, SSL and IPsec support, IEEE802.1x support, Energy Saving Mode</p>

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m<sup>2</sup> if not otherwise mentioned.

**OPTIONS**

**CASSETTE – MY-1037**

530-sheet capacity, A5-A4, 64-176 g/m<sup>2</sup>

**MEMORY EXPANSION – GC-1310**

256 MB Memory expansion

**MEMORY EXPANSION – GC-1320**

512 MB Memory expansion

**SDHC MEMORY CARD – KQ-1003<sup>2)</sup>**

16 GB SDHC card for storage of overlays, fonts and documents

<sup>1)</sup> optional

<sup>2)</sup> e-STUDIO264cs only

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2012 TOSHIBA TEC. DS264csGBEMD1209