



Document Manager

- Compact multifunctional A3 colour system – ideal for up-and-coming businesses
- Excellent colour quality and flexible finishing options which meet your needs
- Individual templates on LCD and in printer driver to allow for efficient and productive workflows
- Environment friendly thanks to improved toner technology

e-STUDIO2050c
e-STUDIO2550c



SAP® Printer Vendor Solution





e-STUDIO2050c
e-STUDIO2550c



<p>General</p>	<p>Print & Copy Speed 20/25 ppm (A4), 10/12 ppm (A3) Warm-up Time Approx. 15 seconds (from low power mode) Paper Size & Weight Cassettes: A5R-A3, 60-163 g/m² Large Capacity Feeder¹⁾: A4, 60-163 g/m² Bypass: 100 x 148 mm-A3, 60-209 g/m²</p> <p>Paper Capacity 250 sheets (Cassettes), 100 sheets (Bypass) Maximum: 2,900 sheets</p> <p>Automatic Duplex Controller Type A5R-A3, 60-163 g/m² Toshiba e-BRIDGE</p> <p>Control Panel 9" (22.8 cm) colour touch panel LCD</p> <p>Memory 8 GB SSD / 2 GB RAM, 160 GB Toshiba Secure HDD^{1) 2)}</p> <p>Interface 10/100/1000BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g)</p> <p>Dimensions & Weight 575 x 590 x 662 mm (W x D x H), ~ 57 kg</p>
<p>Print</p>	<p>Resolution Max. 600 x 600 dpi (5 bit), 600 x 1,200 dpi (1 bit)</p> <p>Page Description Languages XPS, PCL6 and PostScript 3 compatible</p> <p>Supported Systems Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400</p> <p>Print Functions Universal Driver, Driver templates, Driver plug-ins, Hold print³⁾, Print from USB, Tandem printing</p>
<p>Scan</p>	<p>Resolution Max. 600 x 600 dpi</p> <p>Scan Speed Up to 50 ipm (300 dpi)</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF/XPS³⁾/PDF, Slim PDF, Secure PDF, Searchable PDF¹⁾ (and other formats like DOC, XLS, RTF, TXT, PDF/A)¹⁾</p> <p>Scan Functions Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local³⁾), Meta Scan¹⁾, Scan to Box (e-Filing)³⁾, Remote TWAIN, TWAIN1.7/1.8/1.9³⁾</p>
<p>Copy</p>	<p>Resolution Max. 600 x 600 dpi</p> <p>First Copy Colour: Approx. 10.3 seconds BW: Approx. 8.2 seconds</p> <p>Zoom 25-400% (platen), 25-200% (RADF)¹⁾</p> <p>Copy Modes Text, Text/Photo, Photo, Printed Image, Map</p>
<p>Fax¹⁾</p>	<p>Communication Super G3, G3 (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory 100 MB (SSD)/1 GB (HDD)¹⁾ Transmission/Reception</p> <p>Network-Fax Driver for Windows 7/Vista/XP/Server2008 R2</p> <p>Incoming Fax Routing To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing³⁾</p>
<p>System & Security</p>	<p>Device Management e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration</p> <p>System Features e-Filing³⁾ document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 60/12,060³⁾ One-touch Templates for storage of personalised settings or workflows, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip³⁾</p> <p>Accounting & Security Role Based Access, LDAP support, 50/1,000³⁾ department codes & 100/10,000³⁾ user codes, card reader¹⁾, private print³⁾, standard data encryption with Toshiba Secure HDD³⁾, Data Overwrite Enabler^{1) 3)}, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant^{1) 3)}, Scan to Secure PDF</p> <p>¹⁾ Optional ²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed. ³⁾ Requires Toshiba Secure HDD</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.</p>

OPTIONS

PLATEN COVER – KA-1640PC

RADF – MR-3024

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY – MJ-5004

2 inner trays, 150- and 250-sheet capacity

INNER FINISHER – MJ-1036

2 trays, 600-sheet capacity
50-sheet multi-position stapling
482 x 508 x 232 mm (W x D x H), ~ 15.3 kg

SADDLE-STITCH FINISHER – MJ-1037

1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
500 x 642 x 961 mm (W x D x H), ~ 37 kg

HOLE PUNCH UNIT – MJ-6007/MJ-6008

Options for Finisher MJ-1036/MJ-1037
Available in 2-holes (E), 4-holes (F/S)
126 x 464 x 174 mm (W x D x H), ~ 3.3 kg
120 x 597 x 245 mm (W x D x H), ~ 3.4 kg

PAPER FEED UNIT – MY-1040

550 sheets (1 drawer), A5R-A3, 60-163 g/m²
575 x 583 x 163 mm (W x D x H), ~ 9.5 kg

PAPER FEED PEDESTAL – KD-1032

550 sheets (1 drawer), A5R-A3, 60-163 g/m²
668 x 701 x 292 mm (W x D x H), ~ 16.3 kg

LARGE CAPACITY FEEDER – KD-1031A4

2,000-sheet capacity, A4, 64-105 g/m²
668 x 735 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

- DESK – MH-2050
- PAPER FEED CONTROLLER – GH-1080
- DRAWER MODULE – MY-1039
- TOSHIBA SECURE HDD 160 GB²⁾ – GE-1220
- FAX BOARD – GD-1320EU
- FRONT USB KIT – GR-1140
- WORK TRAY – KK-4550
- DATA OVERWRITE ENABLER – GP-1070³⁾
- e-BRIDGE ID-GATE – KP-2004/5, TWN3XX
- WIRELESS LAN MODULE – GN-1060
- META SCAN ENABLER – GS-1010
- IPsec ENABLER – GP-1080
- UNICODE FONT ENABLER – GS-1007³⁾
- e-BRIDGE RE-RITE – GB-1280
- ACCESSIBLE ARM – KK-2550