



Colour Manager

- Professional A3 colour system for demanding requirements
- Designed to perform high volume at high speed
- Superior image quality with brilliant colours for impressive document output
- Intuitive usage of sophisticated technology for smooth operation

e-STUDIO5560c PRO
e-STUDIO6560c PRO
e-STUDIO6570c PRO



**e-STUDIO5560c PRO****e-STUDIO6560c PRO****e-STUDIO6570c PRO**

General	Print & Copy Speed Colour: 55/65/65 ppm (A4), 27/30/30 ppm (A3) Monochrome: 55/65/75 ppm (A4), 27/30/37 ppm (A3) Warm-up Time Approx. 70 seconds from low-power mode Paper Size & Weight Cassettes: A5R-320 x 460 mm, 64-256 g/m ² Tandem LCF ¹⁾ : A4, 64-256 g/m ² Bypass: A6R-330 x 483 mm, 64-300 g/m ² , banner paper (313 x 1,200 mm, 90-163 g/m ²) Paper Capacity 4 x 540 sheets (Cassettes) or 2 x 540 sheets (Cassettes) + 2,320 sheets (Tandem LCF ¹⁾), 100 sheets (Bypass) Maximum: 6,000 sheets Automatic Duplex Controller Type Memory A5R-320 x 460 mm, 64-256 g/m ² EFI Fiery System, Toshiba e-BRIDGE EFI: 80 GB ²⁾ HDD, 512 MB (max. 1,024 MB) RAM e-BRIDGE: 320 GB ²⁾ HDD, 2.0 GB RAM Interface 10/100/1000 BaseT (incl. IPv6), High-Speed USB 2.0 Dimensions & Weight 980 x 698 x 1,540 mm (W x D x H), ~ 252 kg
Print	Resolution 600 x 600 dpi, 8 bit per colour channel 1,200 x 1,200 dpi (2 bit, PostScript driver only) Page Description Languages Adobe PostScript 3, native support for PDF1.4-1.7, PDF/X, TIFF 6.0 and EPS Supported Systems Windows 8/7/Vista/Server 2008/Server 2003 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit), Mac OS X 10.4.11-10.9, Novell Netware (NDPS) Colour Modes Auto-Colour (ACS), Colour, Monochrome Colour Settings ICC based in-RIP colour management: CMYK, RGB, CIE Lab and spot colour support, device ICC link profiles support
Scan	Resolution Max. 600 x 600 dpi, 8 bit per colour channel Scan Speed Colour & Monochrome: 77 ppm (300 dpi) Document Feeder Max. 100 sheets, A5R-A3, 35-209 g/m ² Scan Modes Auto-Colour (ACS), Colour, Greyscale, Monochrome File Formats JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF Scan Functions Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS), Meta Scan ³⁾ , Scan to Box (e-Filing/Mailbox), Scan to "Hold" Queue
Copy	Resolution Scan: 600 x 600 dpi, 10 bit per colour channel Print: 600 x 600 dpi, 8 bit per colour channel First Copy Output Time 2,400 x 600 dpi, Monochrome with smoothing Colour: Approx. 6.5 seconds Monochrome: Approx. 5.3/5.3/4.6 seconds Zoom 25-400% (platen), 25-200% (RADF) Copy Modes Text, Text/Photo, Photo, Printed Image, Map, Image Smoothing Colour Modes Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, Monochrome Colour Settings Hue, Saturation, Colour Balance, RGB Adjustment, 5 One-touch modes
Fax¹⁾	Communication Super G3, G3 - (opt. 2 nd line), Internet Fax T.37 Transmission Speed Approx. 3 seconds per page Compression JBIG, MMR, MR, MH Network-Fax Driver for Windows 8/7/Vista (32/64 bit), Server 2012 R2/Server 2008 R2 (64 bit) Incoming Fax Routing To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing
System & Security	Device Management Command WorkStation for monitoring and managing of print jobs, TopAccess for remote administration and configuration System Features e-Filing document server for secure storage, document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, Print from USB, RIP-while-Print, e-BRIDGE Open Platform ³⁾ , Embedded Web Browser, Job Skip, black overprinting, composite overprinting Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, private print, standard data encryption, Data Overwrite Enabler ³⁾ , IP and MAC address filter, port filter, support of SSL and IPsec protocols, IEEE802.1x support, Scan to secure PDF

OPTIONS**MULTI-STAPLING FINISHER – MJ-1103**

2 trays, 3,250-sheet capacity
 50-sheet multi-position stapling
 A5R-A3, 64-105 g/m² (stapling mode)
 617 x 603 x 1,085 mm (W x D x H), ~ 40 kg

SADDLE-STITCH FINISHER – MJ-1104

2 trays, 3,250-sheet capacity
 50-sheet multi-position stapling
 5-sheet center-folding
 Saddle-stitched booklets of up to 60 pages
 A5R-A3, 64-105 g/m² (stapling mode)
 617 x 603 x 1,085 mm (W x D x H), ~ 70 kg

HOLE PUNCH UNIT – MJ-6102

Option for Finisher MJ-1103/MJ-1104
 Available in 2 holes (E), 4 holes (F), 4 holes (S)
 112 x 573 x 323 mm (W x D x H), ~ 7 kg

LARGE CAPACITY FEEDER – MP-2501A

2,500-sheet capacity, A4, 64-256 g/m²
 360 x 552 x 542 mm (W x D x H), ~ 29 kg

GRAPHIC ARTS KITS

EFI Spot-On, EFI Hot Folders, EFI Auto Trapping

EFI COLOR PROFILER

Proofing Software incl. ES-2000 Spectrophotometer

OTHER OPTIONS

SIDE EXIT TRAY – KA-6550-ET
 FAX BOARD – GD-1270EU-FN
 DATA OVERWRITE ENABLER – GP-1070
 META SCAN ENABLER – GS-1010
 UNICODE FONT ENABLER – GS-1007
 e-BRIDGE Re-Rite – GB-1280

¹⁾ e-STUDIO5560c PRO tandem LCF version only

²⁾ 1 GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

³⁾ Optional

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.

**TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH**

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
 TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
 WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
 Leading Innovation >>>