



PIN OUT

P1		P2
1	_____	11
3	_____	12
5	_____	10
7	_____	8
9	_____	9
11	_____	7
13	_____	5
15	_____	6
17	_____	4
19	_____	19
2	_____	18
4	_____	13
6	_____	14
8	_____	2
10	_____	3
12	_____	1
14	_____	16
16	_____	15
18	_____	17
20	(no connection)	20

NOTES:

- 1.ALL COMPONENTS ARE RoHS COMPLIANT.
- 2.100% OPEN AND SHORT TEST.
- 3.CONDUCTOR RESISTANCE:3 OHMS
- 4.INSULATION RESISTANCE:10 MEGOHMS.
- 5.HI-POT:DC200V/0.01S

⑤	TAG	1PCS	DELTACO TAG
④	HOOD MOLDED	1PCS	BLACK PVC
③	CONNECTOR	1PCS	MINI DISPLAYPORT 20P MALE GOLD PLATED
②	CONNECTOR	1PCS	DISPLAYPORT 20P MALE GOLD PLATED
①	CABLE	1PCS	[(34AWGx1PAIR)+D+FAM]x5+(34AWGx4C)+ AEB BLACK PVC JACKET OD:5.0+0.2mm
NO.	PARTS NAME	Q'TY	SPFCIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	DP-1121-K
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:

MINI DISPLAYPORT CABLE 20P M
DISPLAYPORT 20P M

