Key **Features**

- 100% sRGB wide color gamut coverage
- Hardware color calibration
- Delta E < 2 color accuracy
- · Pre-calibrated uniformity correction
- 21:9 aspect ratio



Product **Description**

With an immersive curved screen and stunning WQHD+ 3440 x 1440 resolution, the ViewSonic VP3481a monitor elevates your viewing experience from flat to panoramic. With Pantone validated 100% sRGB color coverage, and an amazing Delta E<2 value, this 4K monitor provides industry standard color accuracy to ensure superior results, while HDR10 compatibility delivers a wider dynamic range of vivid colors and richer contrast. Thanks to an expansive 34″ frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. Featuring an incredible 100Hz refresh rate and AMD FreeSync™ technology, this monitor delivers smooth, tear-free playback ideal for video editors and game developers. With a sleek and modern design, the VP3481a features a future-proof USB-C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming and gaming. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

Visit Us www.viewsonic.com

DISPLAY		CONTROLS	
Display Size (in.):	34	Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
Viewable Area (in.):	34		
Panel Type:	VA Technology	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual
Resolution:	3440 x 1440	OPERATING CONDITIONS	Image Adjust, Setup Menu
Resolution Type:	WQHD+	Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	3,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	20M:1	WALL MOUNT	20 /0 10 90 /0
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	400 cd/m² (typ)	INPUT SIGNAL	100 X 100 IIIIII
Colors:	16.7M	Frequency Horizontal:	15 ~ 135KHz
Color Space Support:	8 bit true	Frequency Vertical:	24 ~ 100Hz
Aspect Ratio:	21:9	VIDEO INPUT	
Response Time (Typical GTG):	5ms		PCI-E - DisplayPort (v1.4), TMDS -
Response Time (GTG w/OD):	5ms	Digital Sync:	HDMI (v2.0), Micro-Packet - Type C
Viewing Angles:	178° horizontal, 178° vertical	ERGONOMICS	
Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	130
Curvature:	1800R	Swivel:	120°
Refresh Rate (Hz):	100	Tilt (Forward/Back):	-6° / 21°
Adaptive Sync:	FreeSync	WEIGHT (IMPERIAL)	
Blue Light Filter:	Yes	Net (lbs):	24.6
Flicker-Free:	Yes	Net Without Stand (lbs):	16.1
Color Gamut:	Adobe RGB: 89% size / 83% coverage (Typ)DCI-P3: 88% size / 88% coverage (Typ)EBU: 119% size / 100% coverage (Typ)REC709: 120% size / 100% coverage (Typ)SMPTE-C: 130% size / 100% coverage (Typ)NFCS: 85% size (Typ)RGB: 120% size / 100% coverage (Typ)MFC	Gross (lbs):	37.9
		WEIGHT (METRIC)	
		Net (kg):	11.2
		Net Without Stand (kg):	7.3
		Gross (kg):	17.2
Pixel Size:	0.232 mm (H) x 0.232 mm (V)	DIMENSIONS (IMPERIAL) (WX	·
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Packaging (in.):	38 x 14.6 x 20.7
COMPATIBILITY		Physical (in.):	31.9 x 18.91~21.23 x 9.6
PC Resolution (max):	3440x1440	Physical Without Stand (in.):	31.9 x 14.4 x 4.1
Mac® Resolution (max):	3440x1440	DIMENSIONS (METRIC) (WXH	·
PC Operating System:	Windows 7/8/8.1/10 certified; macOS tested	Packaging (mm): Physical (mm):	965 x 370 x 525 809 x 480.46~539.23 x 243
Mac® Resolution (min):	3440x1440	Physical Without Stand (mm):	809 x 366 x 105
CONNECTOR		GENERAL	000 X 000 X 100
USB 3.2 Type A Down Stream:	2		cTUVus, FCC-B, ICES003, Energy
USB 3.2 Type B Up Stream:	1	Regulations:	Star 8.0, EPEAT Silver, CEC, MX-COC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC, UkrSEPRO, UKCA, BSMI, RCM, CCC, China RoHS, China Energy Label
USB 3.2 Type C Up Stream;	1		
DisplayPort Alt mode :	'		
HDMI 2.0 (with HDCP 2.2):	2		
DisplayPort:	1	PACKAGE CONTENTS:	VP3481A x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start
Power in:	3-pin Socket (IEC C14 / CEE22)		
Ethernet LAN (RJ45):	1		
AUDIO			Guide x1
Internal Speakers:	5Watts x2	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
POWER		Marranty	*Warranty offered may differ from
Eco Mode (Conserve):	24.8W	Warranty:	market to market
Eco Mode (optimized):	28.7W	Power Management:	Energy Star standards, EPEAT
Consumption (typical):	33.6W		
Consumption (max):	38.6W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization:	1 Yes		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.